

Air Hydraulic Pumps

▼ Shown: PAM-1041



PAM Series

Reservoir Capacity:
4,0 - 8,0 litres

Flow at Rated Pressure:
0,15 l/min

Air Consumption:
510 l/min

Maximum Operating Pressure:
700 bar




Locking Valves
Pumps with 4/3 manual valves are available with 4/3 manual locking valves instead. Add suffix "L" to pump model number.

Page: 138


- Twin air motor configuration delivers high-flow performance in first stage, up to 14 bar, for rapid cylinder advance
- 4 and 8 litres reservoirs for use with a wide range of cylinders
- Integral shroud protects air motors and provides easy carry.



VA-2 Remote Valve
For remote operation of PAM-Series air pumps. Permits either hand or foot operation.



PAM-Series (mm)



Used with Cylinder	Usable Oil Cap. (litres)	Model Number with Shroud	Pressure Rating (bar)	Output Flow Rate (l/min)		Valve Function	Valve Type	Air Pressure Range* (bar)	Air Consumption (l/min)	Sound Level (dBA)	Weight (kg)
				1 st stage	2 nd stage						
Single-Acting	2,6	PAM-1021	700	10,65	0,15	Adv./Hold/Retr.	3/2	2,7-6,9	510	87	22,7
	7,6	PAM-1022	700	10,65	0,15	Adv./Hold/Retr.	3/2	2,7-6,9	510	87	27,2
Double-Acting	2,6	PAM-1041	700	10,65	0,15	Adv./Hold/Retr.	4/3	2,7-6,9	510	87	22,7
	7,6	PAM-1042	700	10,65	0,15	Adv./Hold/Retr.	4/3	2,7-6,9	510	87	27,2

* Recommended Regulator-Filter-Lubricator: RFL-102.